

Peterbilt Model 367**Vocational****A PACCAR COMPANY**

2010 EPA Emissions Certified Frames	Yes
Rear Wheel Mudflap Hangers	10-5/8", 10-3/4", 11-5/8" or 13-3/8" Steel
Quarter Fenders	Painted or Stainless Steel Hangers
Fifth Wheels	Black Molded or Stainless Steel
Deck Plate Access	Jost or Holland
Front Axles Packages	Left, Right or Both
Front Springs	Dana Spicer 12,000 lb., 13,200 lb, 14,600 lb, 20,000 lb or 22,000 lb. Meritor 12,000 lb or 14,600 lb. Marmon-Harington MT22
Front Hubs	Taper Leaf - Non Driving, Split Progressing Front Driving Axle
Front Brakes	Iron or Aluminum LMS - Non Driving, Iron Front Driving Axle
Single Rear Axles	Air Cam Drum 15"x4", 16.5"x5", 16.5"x6", 16.5"x7" or Air Disc
Tandem Rear Axles	Dana Spicer 21,000 lb, 23,000 lb, 25,000 lb, 26,000 lb, 30,000 lb. Meritor 21,000 lb, 23,000 lb.
Tridem Rear Axles	Dana Spicer 40,000 lb, 44,000 lb, 46,000lb, 52,000lb, Meritor 40,000 lb, 44,000 lb, 46,000 lb,
ABS Systems	Dana Spicer 58,000 lb, Meritor 66,000 lb.
Single Rear Suspensions	Bendix 4S4M, 6S4M or 6S6M Air
Tandem Rear Suspension	Peterbilt AirTrac, Reyco 79KB, 102 or 102AR
Tridem Rear Suspension	Peterbilt FlexAir, Low Air Leaf, Air Leaf, AirTrac or QuadraFlex, Hendrickson HN, HMX or RT, Chalmers 854, Reyco 102 or Neway AD-252
Rear Hubs	Peterbilt Air Trac or Neway AD378
Rear Brakes	Iron or Aluminum LMS or Iron
Engines	Air Cam Drum 16.5"x7", 16.5"x8.6", 18"x7" or Air Disc
Batteries	PACCAR MX, Cummins ISX15
Air Cleaner(s)	PACCAR or Optima
Exhaust System	Cowl Mounted Single or Dual, Single Under Hood
Exhaust Guards	Single or Dual vertical or Horizontal
Transmissions-Manual	Stainless Steel - Vertical
Transmissions-Auto	Fuller 10 or 18 Speed Manual
Tires	Ultrashift
Wheels	Bridgestone or Michelin
Cab	Steel or Aluminum - 22.5" or 24.5"
Hood	Aluminum
Sleepers	Fiberglass
Seats-Driver	36", 48" or 63" Low Roof or 48", 63" or 70" UltraCab
Seats-Passenger	Driver: Peterbilt UltraRide or Atlas
Crew Cab Conversion	Passenger: Peterbilt UltraRide, Atlas or 2 Person
Air Dryers	N/A
Air Tanks	Bendix
Chassis Hose	Steel or Aluminum
Air & Electric Mounting	Nylon or Wire Braid
Fuel Tanks	Back of Cab or End of Frame
Battery Box	20" Aluminum 50 - 60 gallon; 23" Aluminum 50 - 120 gallon; 26" Aluminum 60 - 150 gallon
	Standard Aluminum

Please see your local Peterbilt dealer to use Peterbilt PROSPECTOR to specify options on your particular truck.