



The 6.7-liter PACCAR PX-7 engine delivers superior performance, minimizes operational costs and maximizes uptime for medium-duty customers. Reduced maintenance, long service intervals and excellent fuel efficiency add up to a superior lifetime value.

The PACCAR PX-7 is available in horsepower ratings from 200 to 360hp and offers up to 800 lb-ft of torque.

PEAK HORSEPOWER	PEAK TORQUE (LB-FT @ RPM)	
200	520 @ 1,600	0
220	520 @ 1,600	
220	600 @ 1,600	0
240	560 @ 1,600	0
250	660 @ 1,600	0
260¹	660 @ 1,600	0
280¹	660 @ 1,600	0
3001	660 @ 1,600	0
325 ¹	750 @ 1,800	0
340 ²	700 @ 1,600	0
360²	800 @ 1,800	0
¹ Also Fire Service Rating, ² Fire Service	ce Rating Only	







ENGINE SPEED (RPM)

CONFIGURATION Inline 6-Cylinder
BORE X STROKE (MM) 107x124

DISPLACEMENT 6.7 Liters

DRY WEIGHT 1,150 LBS

OIL SYSTEM CAPACITY 19.5 U.S. Quarts

HORSEPOWER 200-360 HP

GOVERNED SPEED

CLUTCH ENGAGEMENT TORQUE³

400 LB.-FT. @ 700 RPI

BASE WARRANTY⁴

3 YEARS/UNLIMITED MILE

CERTIFICATION

EPA 202

Determined By Engine Horsepower and Idle Setting

4 Extended Protection Plans Available

MAINTENANCE ITEM	MILES	KILOMETERS
FUEL FILTER	60,000	96,000
OIL AND FILTER	30,000 ⁵	48,000
DEF FILTER	200,000	320,000



⁵Duty cycle dependent. Please reference Operator's Manual

Note: Equipment and specifications shown in this procure are subject to change without notice. Consult with your PACCAR Engine distributor at time of ordering for standard and optional equipment. PX-7 is a trademark of PACCAR Inc.

ISIT PACCARPOWERTRAIN.COM TO FIND A LOCAL DEALER

